


## KS59AOE2

Hood, Decorative wall hood, Coloniale, Anthracite, 60 cm, A



### TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 60 cm • Extraction: Extraction • EAN code: 8017709303235

### AESTHETICS

Colour: Anthracite • Aesthetics: Coloniale • Design: Chimney • Components finishing: Antique brass • Material: Heat-moulded • Type of steel: Brushed

### PROGRAMS / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes

### CONTROLS

Control setting: Control knobs • Control knobs: Colonial • No. of controls: 2 • Controls colour: Old Brass

### TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light Power: 1 W • Light color temperature scale (°K): 3000 °K • Free outlet maximum capacity: 820 m<sup>3</sup>/h • Motor power: 275 W • No. of filters: 2 • Anti-grease filters: Stainless steel • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

## PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): A • Fluid Dynamic Efficiency class (FDEC): A • Grease Filtering Efficiency Class (GFEC): D • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEChood): 58 kWh/a • Fluid Dynamic Efficiency (FDE): 29.9 • Lighting Efficiency (LE): 118.2 lux/W • Grease Filtering Efficiency (GFE): 70.8 % • Air flow at minimum speed (Qmin): 311 m<sup>3</sup>/h • Air flow at maximum speed (Qmax): 522 m<sup>3</sup>/h • Air flow at boost speed (Qboost): 754 m<sup>3</sup>/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 49 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 63 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPEboost): 70 dB(A) • Time increase factor (F): 0.9 • Energy Efficiency Index: 52.3 • Measured air flow rate at best efficiency point (Qbep): 418 m<sup>3</sup>/h • Measured air pressure at best efficiency point (Pbep): 443 Pa • Measured electric power input at best efficiency point (Wbep): 172 W • Nominal Power consumption of the light system (WL): 2 W • Average illumination of the light on the cooking surface (Emiddle): 260 lux • Sound power level at highest setting (Lwa): 63 dB(A)

## ELECTRICAL CONNECTION

Electrical connection rating: 277 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

## SPEED 1

Extraction rate IEC 61591: 311 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 49 dB(A) • Power: 199 W

## SPEED 2

Extraction rate IEC 61591: 439 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 231 W

## SPEED 3

Extraction rate IEC 61591: 522 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 62 dB(A) • Power: 260 W

## INTENSIVE SPEED

Extraction rate (IEC 61591): 754 m<sup>3</sup>/h • Noise level IEC 60704-2-13: 70 dB(A) • Power: 280 W

## LOGISTIC INFORMATION

Dimensions of the product (mm): 722x595x484 • Width: 595 mm • Depth (mm): 484 mm • Product Height (mm): 722 mm

## OPTIONAL

FLT6: Charcoal filter, HoodsKITALLFC: Charcoal filter, Hoods

